



Data Sheet - APET Sheet for FFS Machines

Product	APET Sheet
Type of process	FFS machines

Sheet Parameters

Material	Material composition	Structure
APET	recycled / virgin	ABA

Oxygen @25°C dry	ASTM D-3985		
	250	350	450
			[µm]
APET	13	9.5	7
			cc/m ² .day.1atm

All values pertain to the original sheet and not to the final product.

Slip Anti Block	Da	Silicone on one or two sides
Colors	transparent, *opaque , *semi transparent	

*standard colors or as requested by the customer

Width	245 - 1380	[mm]
Thickness (total)	200 - 1200	[µm]

Roll weight & length tolerance	±10%	
Width tolerance	-0	[mm]
	+1	
Thickness tolerance	±3%	average
	±5%	specific point

Roll Property

Max. dia.	Ø1100	[mm]	Ø"
Min. dia.	Ø200	[mm]	
Max. weight	1000	[Kg]	
Min. weight	30	[Kg]	
Core length	+0	[mm]	
	-10		
Core dia. I.D.	Ø3"	Ø6"	carton

Comments

- Roll winding - Sealing layer on inner side.
- Continuity of roll : Max. 1 connection in continuity of roll, the connection is clearly marked.
- Sticker indicate "**Sealing inside**" on each roll.

P.O.Box 53 Shavei Zion, 22806 Israel
 Tel.972-4-98206090 Fax.972-4-9826619
 info@szp.co.il | www.szp.co.il

